

CAPITAL 200



DESCRIPTION

Allowing smooth blending in every architectural background through its modern design and extremely sleek profile, CAPITAL 200 delivers a powerful output from a compact body with outstanding performances. Fitted with a variety of optional high build and design optics groups for the utmost optical efficiency, this versatile floodlight also assures balanced projection and photometric flexibility tailored to the selective demands of the most sophisticated architectural needs. Alternative ON-OFF white light versions available.


MAIN FEATURES

- Max. delivered lm output: 16438 lm / 111 lm/W
- Size: (HxWxD) 276x475x90 mm / 10.8x18.7x3.5"
- Control system: DMX-RDM, DALI DT8, DALI, ON-OFF, 0-10V, on-board or remote wireless data
- Medium-sized floodlight specific for wall wash effects on diverse architectural elements


LED COLOUR CONFIGURATIONS



CAPITAL 200




FEATURES




LED COLOUR CONFIGURATIONS



OPTIONS



FINISHES



MORE INFO



CODES

AL5010 CAPITAL 200
AL5012 CAPITAL 200 POLAR EDITION
AL5036 CAPITAL 200 B

PERFORMANCE	WATT	MAX LM OUTPUT	LM/WATT
CAPITAL 200 RGBW	155	11195	72
CAPITAL 200 DW	148	16438	111
CAPITAL 200 W	148	16370	111
CAPITAL 200 B	148	16370	111

BEAM ANGLE REFERENCE	RGBW	DW/W
SPOT	8°	12°
NARROW	12°	15°
MEDIUM	23°	25°
WIDE	44°	48°
EXTRA WIDE	59°	66°
ELLIPTICAL	9° x 42°	14° x 39°
ELLIPTICAL WIDE	19° x 39°	22° x 37°
WALL WASH	14° (5° incline) x 37°	19° (5° incline) x 37°



Hungary – Puskás Arena, Budapest

