



DUNE MK3



DESCRIPTION

With its IP68 waterproof protection rating, AISI 316L stainless steel body, and smart beam angle tilt orientation adjustment, DUNE MK3 is a highly performing recessed LED uplighter. Specifically designed for exterior in-ground applications, it delivers spot lighting as well as wall grazing effects in exterior recessed applications in both coloured and white light. A 2000 Kg deadweight load capacity makes it suitable for in-ground applications even in vehicular areas.


MAIN FEATURES

- Max. delivered lm output: 2954 lm / 109 lm/W
- Size: (WxD) \varnothing 306x365 mm / \varnothing 12x14.4"
- Control system: DMX-RDM, remote wireless data
- High performance drive-over uplighter with smart beam angle orientation adjustment


LED COLOUR CONFIGURATIONS




DUNE MK3



+/- 10° TILT



230mm
[9 1/8\"]



345 mm
[13.6\"]

306 mm
[12\"]

365 mm
[14.4\"]

FEATURES



DMX - RDM



CLASS



DRIVE
OVER



2000 KG
MAX LOAD



IP68
-1.5m



IK10



7.9 KG



OPTIONS



POLAR



REMOTE
WIRELESS DATA



ANTI-SLIP



ETL
PENDING

LED COLOUR CONFIGURATIONS



RGB+W
3000K



RGB+W
4000K



DW
2700/6500K



WARM
WHITE 2700K



WARM
WHITE 3000K



NATURAL
WHITE 4000K

MORE INFO ON WWW.GRIVEN.COM

CODES

AL5003 DUNE MK3

PERFORMANCE	WATT	MAX LM OUTPUT	LM/WATT
DUNE MK3 RGBW	27	1274	47
DUNE MK3 DW	27	2648	99
DUNE MK3 W	27	2648	99

BEAM ANGLE REFERENCE	RGBW	DW/W
SPOT	7°	12°
NARROW	12°	15°
MEDIUM	21°	25°
WIDE	43°	47°
EXTRA WIDE	66°	61°
ELLIPTICAL	11° x 40°	14° x 39°
ELLIPTICAL WIDE	20° x 40°	23° x 37°



Poland – Presidential Palace Orangery, Warsaw